

**TECHNICAL DATA SHEET**

JANUARY 2009

ALKYDEM* FAÇADE ACRYLATE LATEX PAINT**Description:**

Universal façade latex paint with excellent coverage, good flow, light-fast and weather-resistant, designed for exterior application.

Suitable substrates: sound coatings of old façade latex paint, cement and lime-cement plasters, concrete.

Substrate preparation:

- **for new surfaces** - mandatory priming with ALKYDEM* Acrylate primer for dispersion paints.
- **for surfaces painted before** - for repainting over coatings of old façade latex paint the only preparation is washing from dust.

Application: stir the product well before use. On the prepared surface apply with a brush, roller or sprayer 2 or 3 coats of the acrylate latex paint. Each successive coat can only be laid on after the previous coat is completely dry. Painting can be done at air temperature not lower than 5°C. Thin with water up to 15%.

Theoretical rate of coverage: 150-180 g/m² per coat when the substrate is well prepared.

Cleaning of equipment: with water.

Technical data:

Appearance of paint after stirring:	homogenous, thixotropic mass
Appearance of the film	flat, matt
Relative density, g/cm ³ at 23±2°C	1.5
Drying time to stage V (no peeling) at 23±2°C in h, no more than	5
pH-value, no less than	8
Solubility in water	miscible in any ratio

Storage: at temperatures above 5°C, keep from freezing.



12 months

VOC information: 2004/42/II A(c)40/40

The maximum content of VOC for this product (cat.A/c) is 40 g/l.

Health and safety: This product is not hazardous to health. For more information concerning health and safety, please look up the safety data sheet for this product.

***Trade mark of Body Color OOD**